



TECHNICAL SPECIFICATIONS

Length outside/inside	11.305 mm/11.025 mm
Width outside/inside	2.550 mm/2.480 mm
Height outside/inside	4.000 mm/2.700 mm
Loading height side front/rear	2.610 mm
Loading height back doors	2.610 mm
5th wheel height	1.150 mm
Own weight	22.000 kg
Axle load	10.000 kg
Kingpin pressure	12.000 kg
Axles	BPW 1x10 ton TRIDEC max 25°
Distance kingpin to back axle	7.400 mm
Tire size	4 pcs 275/70 R22.5
Sliding roof	Edscha 125 mm
Chassi neck height	130 mm
Roof	35 mm
Front wall in steel	

EQUIPMENT

Stanchion holes 6x3 pcs
Stanchions 6 pcs
Multilock side rave
Ferry shackles
ADR-sign
Floor in 30 mm plywood
- max 5.460 kg truck load
Spare wheel carrier
Tail lift 2.000 kg
Self-steering axle Triddec max 25°

OPTIONAL

Lifting roof 500 mm
Drop sides 750 mm
Drop sides 550 mm
Easy Tarp curtain stand
Central pneumatic opening/ locking
Alu planks
Tool box
30, 33 pallets length



HERE ARE PNO TRAILERS, DEPOTS AND WORKSHOPS

PNO SVERIGE AB HELSINGBORG GOTHENBURG JÖNKÖPING MALMÖ
+46 42-499 15 50
www.pno.se

SUB-DEPOTS
ÅKERS STYCKEBRUK
ÖREBRO