



## TECHNICAL SPECIFICATIONS

Length external/internal	7.860 mm/7.700 mm
Width external/internal	2.550 mm/2.480 mm
Height external/internal at a 5th wheel height of 1.150 mm	4.023 mm/2.650 mm
Loading height side	2.570 mm
Loading height/width rear doors	2.650 mm/2.480 mm
Overall length in touring position	10.670 mm
5th wheel height, two heights	1.050/1.150 mm
Own weight	6.720 kg
Max load	29.280 kg
Total weight	36.000 kg
Axle load	20.000 kg
Kingpin load	16.000 kg
Axles	BPW 2x10ton drum brakes
Distance axles	1.820 mm
Brakes	EBS - can router
Tire size	265/70 R19.5
Chassi neck height	180 mm
Aluminium profile front wall and rear doors	
Roof	35 mm
Roof frame TSE sliding roof	113 mm

## EQUIPMENT

Lashing rings in side rave  
Ferry schackles  
ADR-sign  
Hardwood floor 28 mm with steel sections  
Stanchion equipment 1x3 post pockets

## OPTIONAL

Lifting roof 400 mm  
Domestic height  
Alu planks  
Tool box  
Full pallet width all the way from the the bottom and to the top.



HERE ARE PNO TRAILERS, DEPOTS AND WORKSHOPS

PNO SVERIGE AB HELSINGBORG GOTHENBURG JÖNKÖPING MALMÖ  
042-499 15 50  
www.pno.se

SUB-DEPOTS  
ÅKERS STYCKEBRUK, ÖREBRO